



GOESOL™ BLACK **ACRYLIC LATEX FENCE & BARN PAINT**

DESCRIPTION:

Premium Quality Acrylic fence paint designed to beautify and protect Post & Rail Fences, Stables, barns and more. Environmentally friendly water-based formula.

Application Methods:

Brush – Roller – Spray

DIRECTIONS: Surface shall be clean, dry and free of any dirt or contaminants. For best results, pressure wash the surface you want to paint beforehand to remove, dirt, moss or other contaminants and allow surface to dry out completely before applying GOESOL™. Before applying, **STIR CONTAINER THOROUGHLY. (A drill mounted paint mixer is highly recommended for correct mixing)** Apply by brush, roller or airless spray. Clean tools with water immediately after use. Be sure to wear eye protection and gloves when mixing and applying this product.

IMPORTANT: Application temperature must be a minimum of 10°C and rising. Do not apply when temperature is expected to drop below 10°C within a 24- hour period. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

COVERAGE: Up to 2.3 - 2.5 square metres per litre per coat depending upon porosity of surface.

DRYING TIME: Dry to the touch in 2-3 hours. Allow 6-8 hours before applying second coat.

CLEAN UP: Clean tools with soap and water before material has dried.